

PRODUCT	43020
USE	Paper, cardboard and other porous materials.
PROPERTIES	Adhesive with low viscosity and short open time, it is optimal for packaging applications but can also be used to bond many different substrates like wood, fabrics, glass, ceramics and certain plastics.
DESCRIPTION	Basis: EVA & synthetic resins Composition: Non-hazardous according to Directive 1999/45/CE Color: Amber / Brown Diameter: Ø 43,1 ± 0,40 mm Long: 43 mm ± 3 mm
TECHNICAL DATA	Viscosity (180 °C): 4.000 ± 1.200 CP Softening time: 102 ± 6 °C Application temp: 170 °C - 210 °C Open time: 15" - 20" (short) Bond time: 10" - 12"
PACKAGING	Box 10 kg Pallet 480 kg
INFORMATION	All components of this product comply with the requirements of Regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food, and are approved for use in adhesives for indirect food contact by the Food & Drug Administration (Code of Federal Regulations, Title 21, Section 175.105 "Adhesives").
REVIEW 5 / 5 / 2014	

COMERSIM S.A.U.

Pol. Ind. "Ampliación Comarca 1", Calle L 15 - 17
31160 ORKOIEN - Navarra - Spain

T +34 948 33 04 12
F +34 948 33 02 53

simes@grupodesa.es
www.simes.es

EXPORT

export@grupodesa.es
www.simes.es/hotmelt/en

T +34 948 33 52 66
F +34 948 33 02 53



Management
System
ISO 9001:2008

www.tuv.com
ID 1100008007

