

PRODUCT	10084
USE	Bonding of large areas.
PROPERTIES	Adhesive with permanent tack and low viscosity, optimal for spraying applications.
DESCRIPTION	Basis: Rubber Composition: Non-hazardous according to Directive 1999/45/CE Color: Amber / Brown Format: Easy melt
TECHNICAL DATA	Viscosity (180 °C): 800 ± 300 CP Softening time: 70 ± 5 °C Application temp: 140 °C - 170 °C Open time: Permanent Bond time: -
PACKAGING	Industrial
INFORMATION	All components of this product comply with the requirements of Regulation (EU) No 10/2011 on plastic materials and articles intended to come into contact with food, and are approved for use in adhesives for indirect food contact by the Food & Drug Administration (Code of Federal Regulations, Title 21, Section 175.105 "Adhesives").
REVIEW 5 / 5 / 2014	

COMERSIM S.A.U.

Pol. Ind. "Ampliación Comarca 1", Calle L 15 - 17
31160 ORKOIEN - Navarra - Spain

T +34 948 33 04 12
F +34 948 33 02 53

simes@grupodesa.es
www.simes.es

EXPORT

export@grupodesa.es
www.simes.es/hotmelt/en

T +34 948 33 52 66
F +34 948 33 02 53



Management
System
ISO 9001:2008

www.tuv.com
ID 1100008007

